

型号: 4K280-9HSD-SCH-CO

技术参数



产品名称	28" 4K(3840×2160)箱载式导演监视器4画面分割显示		
型号	4K280-9HSD-SCH-CO		
屏幕尺寸	28"		
分辨率	3840×2160 pixels		
点距	0.16 (H) x 0.16 (V) mm		
色彩	1.073G (10 bits)		
屏幕比例	16:9		
亮度	300 cd/m ²		
对比度	1000:1		
背光源	LED		
响应时间	Tr = 1.5ms; Tf = 3.5ms		
可视角度	170°(H) / 160°(V)		
输入	HDMIx4 (HDMI2.0x1 support 4K 60HZ; HDMI1.4x3 support 4K 30HZ)		
音频	DVI, VGA, Audio (L/R), Tally, USB Upgrade		
	耳机孔, 扬声器		
HDMI 支持格式	HDMI 2.0 4K UHD 2160P (23.98/24/25/29.97/30/50/59.94/60)		
	HDMI 1.4 4K UHD 2160P (23.98/24/25/29.97/30)		
	480i/576i/480p/576p		
	720p (60/59.94/50/30/29.25/24/23.98)		
	1080i (60/59.94/50)		
	1080p (60/59.94/50/30/29.97/25/24/24sF/23.98/23.98sF)		
内置SDI⇌HDMI互转			
信号转换	SDI to HDMI, SDI to SDI, HDMI to SDI, HDMI to HDMI		
SDI 信号转换支持格式	3G-SDI:1080P(60/59.94/50)		
	HD-SDI:1080P(30/29.97/25/24)		
	1080I(60/59.94/50)		
	1080PsF24		
	720P(60/59.94/50/30/25/24)		
HDMI 信号转换支持格式	SD-SDI:576I(50),480I(60)		
	1080P(60/59.94/50/30/29.97/25/24)		
	1080I(60/59.94/50)		
	1080PsF24		
	720P(60/59.94/50/30/25/24)		
	576I(50),480I(60)		
消耗功率	≤45W		
输入电压	DC10~24V		
工作温度	-10°C~50°C		
储藏温度	-20°C~60°C		
单机尺寸	731L×410H×39D (mm) (不含铝箱) / 780L×470H×250D (mm) (含铝箱)		
单机重量	21.7kg (含铝箱)		
功能			
*SDI-HDMI双向互转			
*多画面显示 (1P, 2P LR, 2P TB, 2P PIP, 4P)			
*辅助辅助对焦			
*过扫描			
*显示旋转 (0°, 90°, 180°, 270°)			
*单色显示(红, 绿, 蓝)			
*画面静止			
*图像放大			
*点对点			
*中心标记			
*框型标记 (80%, 85%, 90%, 93%, 96%)			
*线条颜色 (红, 绿, 蓝, 白)			
*色温调节			
*3色Tally 指示灯 (红, 绿, 黄)			
标配		选配	
5A 电源适配器	安东电池背扣	装箱件数	1pcs
V型电池背扣		外箱尺寸	84x51x31CM
迷你HDMI线		毛重	24kg
TALLY转接套件			
铝箱			
遮阳罩			
说明书			